



SL srl • www.s-line.it

Via dell'Artigianato 13/15, 20882 Bellusco (MB) Italy
Ph. +39 039 6011239 • Fax+39 039 2124935 • E-mail: info@s-line.it
P.IVA 06386430968 • Codice SDI: USAL8PV

ISO 9001 ISO 14001



CONFORMABLE

January 2024

Description:

Antislip tape composed by aluminum backing coated with corundum fine mineral granules 60 grit and modified acrylic solvent adhesive. The aluminum backing make this product able to adapt to the surfaces in formidable way and it's suitable to make sure irregular surfaces and curves such as knurled aluminum ladders, ramps, grids, etc. Recommended to indoor and outdoor applications, excellent resistance against trampling and good resistance to weathering, UV rays, oils detergents and solvents. Available in rolls and die-cut strips form and in black or yellow colours. Apply to clean and dry surface.

Technical data sheet:

Product	Antislip tape
Adhesive	Modified acrylic solvent
Carrier	Aluminum carrier coated with corundum fine mineral granules
Grit	60
Liner	PET film
Liner color	Transparent
Peel adhesion (PSTC1)	15 +/- 2 N/25 mm
Rolling ball test (PSTC6)	1 cm
Applied weight	860 gr/m ²
Holding power	≥ 48 hours
Static coefficient of friction	Dry leather: 1,11 Wet rubber: 1,40
Dynamic coefficient of friction	Dry leather: 0,84 Wet rubber: 1,12
Impermeability	12 months
Temperature resistance	-30°C + 110°C
Application temperature	Between 18°C and 35°C
Shelf life	12 months
Outdoor age resistance	1-3 years under average walkway conditions

Ageing in following liquid immersion:

Water or detergents	Over 72 hours
Petrol or fuel	Over 72 hours
Diesel oil	6 hours
Brake oil	10 hours
Engin oil	30 hours
Bum test	5,5" char at 1000°C for 4 minutes, will not sustain after flame is cut off.

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.