



**SL srl • [www.s-line.it](http://www.s-line.it)**

Via dell'Artigianato 13/15, 20882 Bellusco (MB) Italy  
Ph. +39 039 6011239 • Fax +39 039 2124935 • E-mail: [info@s-line.it](mailto:info@s-line.it)  
P.IVA 06386430968 • Codice SDI: USAL8PV

ISO 9001 ISO 14001



## Pastel Line

January 2024

### Description:

*Writable coloured adhesive paper, coated with a special removable and repositionable adhesive. Product designed to take notes, highlight, etc. Usable with 3 practical dispensers for home, office, school, car, camper, truck, etc. The entirely adhesive surface guarantees excellent seal, easy removal residue-free and the ability to attach and detach the adhesive sheet several times, without losing adhesiveness.*

### Features and applications:

- 100% recycled paper.
- Good initial tack.
- Quick and easy to use.
- Writable.
- Excellent resistance to aging, UV rays and temperature.
- Repositionable.
- Good adhesion on all surfaces.
- Residue-free.
- Does not damage surfaces.

### Technical data sheet:

<b>Product type</b>	Single sided tape
<b>Adhesive</b>	Removable water-based acrylic
<b>Carrier</b>	100% recycled paper in different colours
<b>Core</b>	Black regenerated polyethylene
<b>Thickness (white)</b>	80 g\m2
<b>Thickness (other colours)</b>	65 g\m2
<b>Application temperature</b>	+ 18°C
<b>Shelf life</b>	24 months

### Colours available:

*Yellow, green, pink, light blue, white, khaki orange, red, kiwi green, light violet.*

### SL dispenser available and standard sizes of refills roll:

**Tack-it:** Dispenser for table, refills roll available in size 60 mm x 10 m

**Tack-it Note:** Dispenser for table and wall, refills roll available in size 60 mm x 10 m

**Tack-it Car:** Dispenser for motor vehicles, refills roll available in size 45 mm x 10 m

The above performance features are based on the results of tests and careful calculations. They are put forward in good faith but are not guaranteed. The enduser should check the suitability of the product for its intended use and consult us for any doubt about particular applications. Storage should be in dry, well ventilated rooms with a temperature around 20°C and protected from continuous exposure to direct sunlight. Always apply the product to clean and dry surfaces.